

Level indicator Unimes



Benefits

- No power supply required
- Reference pointer for easy consumption monitoring
- Measured values are displayed in % liquid level
- Mounting flexibility due to connection threads G1½ and G2
- Materials resistant to biofuel and biodiesel with max. 100 % FAME



Application

For continuous level measurement in tanks containing fuel oil EL, diesel fuel, biodiesel and other low-viscosity media which do not attack materials of the indicator. For tank heights from 900 to 2,000 mm.

Versions

	Part no.
Level indicator Unimes	11500

Blue part no. = in-stock items

Description

Universal mechanical level indicator with fully adjustable brass and nickel silver movement. The pointer deflection amounts to 280° at tank heights and diameters from at least 900 mm to 2,000 mm maximum. Indication in percentage of liquid level, litre scale can be retrofitted. With reference pointer for consumption monitoring.

Technical specifications

Measuring range (tank height)

0/900 to 0/2,000 mm

Scale (displayed values)

0/100 % liquid level

Connection thread

G1½ and G2

Housing/float

Indicator: ABS, impact-resistant

Window: SAN

Float: PE-HD, Ø 41 mm

homershams

Phone: 03 358 8309 or 0800 659 888
 info@homershams.co.nz
 www.homershams.co.nz